



www.bunsen.es



BI-DISTILLER 4L. Ref. BA1040

GENERAL CHARACTERISTICS

- * Model designed as a cabinet shape. Fully automatic continuous output.
- * For usual bi-distillation in laboratory obtaining high quality distillation with high purity water and free of metal ions and pyrogens.
 - * The different parts made of borosilicate glass and heater protected by a quartz sheath lengthens its duration.
 - * This model has wall mounting bracket and incorporate level detector for external tank.
 - * Translucent color screen that displays the process, and easily removable in order to access into the water still.
- * Water consumption; 2L/min. Conductivity at 20°C ($\mu\text{S}/\text{cm}$); 0,5.
- * Safety:
 - * Device protects the water still in the event of water supply failure.
 - * His range incorporates a device to fill a container without worrying when it finished. It cuts water and electrical supply to avoid useless expenses of water and electricity.

Manufactured according to EC directives

Ref	Capacity	Voltage	Dimensions W x H x D (mm)	Weight	Power (W)
BA1040	4 L/h	230 V. 50/60 Hz. 26 A	690 x 480 x 400	22 Kg.	6000



BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fa. +34 916 128 254
info@bunsen.es - www.bunsen.es

