



www.bunsen.es



THERMOSTATIC BATH 3L

Ref. 1600

GENERAL CHARACTERISTICS

- * Double wall construction: the exterior made of aluminum painted in epoxy and the interior basin made of 18/10 stainless steel.
- * Heating by a heating element shielded by AISI 316 stainless steel.
- * Temperature regulation from room temperature up to 120°C by bulb thermostat.
- * Equipped with a safety thermostat that has a manual reset in accordance with DIN12877, class 2.
- * Incorporates a heating element cover tray.
- * Control panel includes:
 - * Illuminated ON switch.
 - * Indicator light showing heating element operation.
 - * Safety thermostat indicator light.
 - * Temperature adjustment selector.

Manufactured according to CE directives.



BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es



Ref	Capacity (l)	Power (W)	Useful measures (Ø x H)	Ext. measures (Ø x H)	Max. temp. (°C)	Stability (°C)
1600	3	500	180 x 120 mm.	245 x 245 mm.	120	±1

Ref	Accessories
1600-1	Raks for 21 test tubes (up to Ø 16 mm)
1600-2	Set of reduction disks
1600-3	Liquid level indicator
1600-4	Raks for 25 test tubes



BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es

