



<u>www.bunsen.es</u>





115L. DRYING OVEN WITH NATURAL AIR CONVECTION Ref. 8322 Plus

GENERAL CHARACTERISTICS

- * Interior and exterior construction in stainless steel AISI 304.
 - * Solid door, fitted with a key. Excellent thermal insulation.
- * Protection against overtemperature class 3.1 according to DIN 12880.
 - * Large (7"), clear, full colour touch screen.
 - * LAN, USB ports and WiFi for communication and data transfer.
 - * Multi-segment time and temperature programs.
 - * Loop function up to 255 times or endless.
 - * Adjustable start delay feature. Adjustable ramps.
- * Recording of min, average and max temperature value for each segment.
 - * Operating in temperature or time priority mode.
- * Temperature sensor fail alarm. Possibility of temperature calibration by the User.
 - * Power failure control system (program continued after restoring power).
 - * Overview of data in tabular and graphic form.
 - * Visual and sound alarm.
 - * Administrating functions for management.
 - * Password protected log-in.Internal memory for programs and data storage.
 - * Operating with gloves on. Event registry with user notifications.





- * Alarm Bar quick visual information about device status.
- * Quick Note user can save messages (50 characters) in Smart PRO controller memory.
 - * Quick Change of parameters: temperature, humidity, time, air flap and fan.
- * Trays made of stainless steel wire; 2 tray included, maximum capacity; 7. Max shelf workload 25 kg. Consult accessories.

Manufactured according to CE directives.

Ref.	Capacity	Dimensions W x H x D	Useful measures W x H x D	Weight	Temperature	Nominal power
8322P	115L.	650 x 850 x 710mm.	460 x 540 x 450mm.	65 Kg.	Up to 300°C	2500

Ref	Accesories	
8300-02		Stainless steel wire shelf INOX
8300-03		Perforated shelf
8300-04		Reinforced shelf
8300-05		Reinforced version
8300-06	♦	Stainless steel cuvettes
8300-07	兩	Table with wheels
8300-08		Additional Pt 100 temperature sensor
8300-09		HEPA-fresh air filter
8300-10		Wheels
8300-11		Non-standard access port for external sensor





