www.bunsen.es

BATH WITH CIRCULATION 200ºC.

Ref. 1802-27

GENERAL CHARACTERISTICS

Equipment designed to temper liquids, formed by a combination of immersion thermostats and a covered basin in order to provide better uniformity of the desired working temperature:
It includes:

* A double-walled metal basin. The interior is 18/10 stainless steel and the exterior is AISI 304 stainless steel.
* TFB immersion thermostat positioned on the cover with an external cooling coil in order to work at a temperature close to the ambient temperature, and it includes a stirring pump with an outlet for external circulation, adjustable by an incorporated tap.
* Digital temperature control by digital thermostat controlled by microcontroller from environment + 5º to 200ºC. Resolution, 0.1ºC.
* Equipped with a safety thermostat adjustable that has a manual reset in the event of over-temperature in accordance with DIN 12877 clase 2.
* Drain tap.
* It incorporates a blank cover to completely shut off the basin.

Manufactured according to CE directives.

Ref	Probe	Power	Useful dimensions W x H x D	Ext. dimensions W x H x D	Max. temp	Precision ºC
1802-27	PT-100	2000W.	210 x 200 x 290mm.	550 x 230 x 350mm.	200ºC	±0.5%

BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fa. +34 916 128 254
info@bunsen.es - www.bunsen.es

Más baños
Other baths