www.bunsen.es

THERMOSTATIC BATH 20L.

Ref. 1606

GENERAL CHARACTERISTICS

* Double wall, metal construction: exterior painted in epoxy with antioxidant treatment and interior basin made of 18/10 stainless steel.
* Heating by shielded heating element made of AISI 316 stainless steel.
* Temperature regulation from room temperature up to 120ºC by bulb thermostat.
* Equipped with a safety thermostat adjustable that has a manual reset according to DIN 12877, class 2.
* Control panel includes:
    * Illuminated ON switch.
    * Indicator light showing heating element operation.
    * Safety thermostat indicator light.
    * Temperature control.

Manufactured according to CE directives.

BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es

BUNSEN

Ref	Capacity	Weight	Power	Useful measures (W x H x D)	Ext. measures (W x H x D)	Temp. Máx	Stability
1606	20L.	8 Kg.	1700W.	490 x 150 x 290mm.	560 x 200 x 440mm.	120ºC	±1ºC

Ref	Accessories
1632	Stainless steel cover with 6 openings and reduction disks
1642	Top cover
1652	Element cover
1662	Blank cover
1663	Drain tap
1680	Hinge for top cover ref. 1642
CHB 062	Racks for baby bottles (18 baby bottles)
1600-10-1	Racks (265x120 mm) for 98 test tubes, Ø 10-12 mm
1600-10-2	Racks (265x120 mm) for 72 test tubes, Ø 14-16 mm
1600-10-3	Racks (265x120 mm) for 50 test tubes, Ø 18-20 mm
1600-3	Liquid level indicator (factory installed)
	Different platform sizes upon client's request

Más baños Other baths

BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es