www.bunsen.es

INMERSION THERMOSTAT TIP 200ºC.

Ref. 1812

GENERAL CHARACTERISTICS

Equipment designed for temper liquids in differents basins with a minimum depth of 150 mm or in order to measure and record the temperature of other, external devices on a closed circuit.

* Clamp fastening system, which allows working even with cylindrical containers.
* Possibility of coupling to the pump an outlet for external circulation.
* All elements in contact with the liquid are manufactured out of AISI 304 stainless steel.
* Stirring pump with the capacity to homogenize the temperature in containers with a capacity of up to 50 liters (relative to water and with the container covered).
* Digital Temperature control by digital thermostat controlled by microcontroller from environment + 5º to 200ºC. Resolution, 0.1ºC.
* Temperature regulation by means of a digital thermostat with auto-adjustable PID control (AUTOTUNIG), in order to obtain very low working temperature inertia.
* Temperature display with double digital display of 4 digits.
* Shielded heating element made out of AISI 316 stainless steel.
* Equipped with a safety thermostat adjustable that has a manual reset in the event of over-temperature in accordance with DIN 12877 clase 2.

Manufactured according to CE directives.

BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es

BUNSEN

Ref	Probe	Power	Resolution (ºC)	Max. temp	Precision ºC
1812	PT-100	2000W.	0,1	200ºC	±0.5%

Ref	Accessories	Capacity	Useful dimensions W x H x D	External dimensions W x H x D
1830	Metal basins	9L.	290 x 150 x 220mm.	380 x 180 x 290mm.
1831	Metal basins	12L.	320 x 150 x 290mm.	380 x 180 x 350mm.
1832	Metal basins	20L.	480 x 150 x 290mm.	550 x 180 x 350mm.
1833	Metal basins	27L.	480 x 200 x 290mm.	550 x 230 x 350mm.
1834	Methacrylate basins	50L.	600 x 200 x 480mm.	670 x 230 x 550mm.
1840	Methacrylate basins	10L.	165 x 160 x 400mm.	173 x 158 x 408mm.
1841	Methacrylate basins	13L.	230 x 160 x 400mm.	238 x 158 x 408mm.
1842	Methacrylate basins	30L.	300 x 200 x 500mm.	308 x 208 x 508mm.
1663	Drain tap for coupling to metal basins			
1664	Pump outlet tap for external circulation in order to couple to the TIP			
	Double body metal basins, stainless steel 18/10 interior, stainless steel AISI 304 exterior. Other capacities basins available upon request.			

Más baños

Other baths

BUNSEN SA. C/ Río Alberche, 30, - 28970 - Humanes de Madrid, Madrid. SPAIN
Tlf. +34 916 113 584 - Fax. +34 916 128 254
info@bunsen.es - www.bunsen.es